

Safety Data Sheet

According to Regulation (EC) N° 1907/2006 (REACH); 453/2010/EC

1. Identification of the substance or mixture and of the company name

Trade Name VT51 hp -30°C

Typical Applications Coolant – Antifreeze, Heat Transfer Fluid.

Company AKOTEC Produktionsgesellschaft mbH

Grundmühlenweg 3 D-16278 Angermünde Tel.: 03331 25 716 30 Mail: info@akotec.eu

Information Department:

Sales / Technical Department

Mail: info@akotec.eu

Emergency information center:

next poison control center or Tel: +49 (0)551 19240

2. Identification of hazards

2.1. Classification of the substance or mixture

No particular hazards known.

Classification according to Regulation (EC) No. 1272/2008 [CLP]: The product is not subject to classification

2.2. Label elements

Label according to Regulation (CE)N° 1272/2008 [CLP]: The product is not subject to labeling

3. Composition / information on ingredients

Propylene Glycol with corrosion inhibitors.

06/2017 Safety Data Sheet VT 51 hp Seite 1 von 11

AKOTEC Produktionsgesellschaft mbH | Grundmühlenweg 3 | D - 16278 Angermünde

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



Chemical name CAS-No CEE number %

1,2-Propanediol 57-55-6 200-338-0 45

4. First aid measures

General advice Remove contaminated clothing.

On contact with eyes Wash affected eyes for at least 15 minutes under

running water with eyelids held open.

On skin contact Wash thoroughly with soap and water.

If difficulties occur after vapor/aerosol has been inhaled

remove to fresh air and seek medical attention.

On Ingestion Rinse mouth and then drink water (two glasses at the

most). Consult doctor if feeling unwell.

Note to physician Symptomatic treatment (decontamination, vital functions),

no known specific antidote.

5. Fire-fighting measures

Suitable extinguishing media: Water spray, alcohol resistant foam, dry

extinguishers, carbon dioxide (CO₂)

Specific hazards Evolution of fumes/fog. The substances/group of

substances mentioned can be released in case of fire.

Vapors heavier than air.

Special protective equipment In case of fire, wear a self-contained breathing

apparatus.

Further Information The degree of risk is governed by the burning

substance and the fire conditions. Contaminated extinguishing water must be disposed according to

official regulations.

6. Accidental release measures

06/2017 Safety Data Sheet VT 51 hp Seite 2 von 11

T: +49 (0) 3331 25 71 63 0 $\,$ I $\,$ F: +49 (0) 3331 25 59 99 6 $\,$ I $\,$ M: info@akotec.eu $\,$ I $\,$ W: akotec.eu



Personal precautions: Use personal protective clothing.

Do not inhale vapors/aerosol.

Environmental precautions: Do not discharge into drains, surface

waters, ground water.

Methods for cleaning up/taking up: <u>Large amount</u>: Pump off products.

Residues/spills: Bind the liquid by using a suitable absorbent material and dispose it

according to the regulations.

7. Handling and storage

Handling Ensure thorough ventilation of stores and working areas.

Protection against fire and explosion.

Take precautionary measures against static discharges. If exposed to fire, keep containers cool by spraying with

water.

Product is hygroscopic. Containers should be stored **Storage**

> tightly sealed in dry place. Since zinc is not compatible with propylene glycol, storage in galvanized containers is

not recommended.

8. Exposure controls and personal protection

General safety and hygiene measures: Wash hands and forearms after handling.

Do not smoke, eat or drink during

manipulations.

Personal protective equipment:

Respiratory protection: Only in case of release of fumes/fog. Well ventilated areas

are recommended for manipulation.

Required when vapors/aerosols are generated. Filter A- (P2) Chemical resistant protective gloves are recommended.

Hands:

Eyes: Safety glasses with side-shields.

DNEL (Workers):

06/2017 Safety Data Sheet VT 51 hp Seite 3 von 11

AKOTEC Produktionsgesellschaft mbH I Grundmühlenweg 3 I D - 16278 Angermünde

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



Substance		Aci	ute	Lo	ng Term
		Systemic	Local	Systemic	Local
1,2 Propanediol	Ingestion	Not relevant	Not relevant	Not relevant	Not relevant
CAS 57-55-6	Skin Contact	Not relevant	Not relevant	Not relevant	Not relevant
CE: 200-338-0 Inhalation		Not relevant	Not relevant	186 mg/m³	10 mg/m³

DNEL (Consumers):

Substance		Ac	ute	Long Term		
		Systemic	Local	Systemic	Local	
1,2 Propanediol	Ingestion	Not relevant	Not relevant	Not relevant	Not relevant	
CAS 57-55-6	Skin Contact	Not relevant	Not relevant	Not relevant	Not relevant	
CE: 200-338-0	Inhalation	Not relevant	Not relevant	50 mg/m³	10 mg/m^3	

PNEC Values

Substance	Fresh Water	Sea Water	Water (Intermittent Releases)	Fresh Water Sediment	Sea Sediment	Soil	Sewage Treatment Plant
1,2 Propanediol	260 mg/l	26 mg/l	183 mg/l	572 mg/Kg dry	57,2 mg/Kg dry	50 mg/Kg dry	20.000 mg/l

9. Physical and Chemical properties

Physical stateLiquidColortranspar

Color transparent Weak, characteristic.

pH 8,5-9,5

Boiling point/range aprox.104°C

Solidification temperature -30°C

Vapor pressure at 20°C 0.1 mbar a 20°C

Flash point $>100^{\circ}\text{C}$ Lower explosion limit 2,6% V/VUpper explosion limit 12,6% V/VIgnition temperature $>200^{\circ}\text{C}$

Density 1.03-1.04 g/cc at 20°C

Solubility in waterUnlimited.

Solubility in other solvents Soluble in polar solvents.

06/2017 Safety Data Sheet VT 51 hp Seite 4 von 11

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



10. Stability and reactivity

Hazardous reactions No hazardous reactions if stored and handle as prescribed.

Substances to avoid Powerful oxidizing agents and strong acids.

Hazardous decomposition products No hazardous decomposition products if

stored and handle as prescribed.

11. Toxicological information

1,2 Propanediol data:

Acute Toxicity:

Exposure	Parameter	Test	Value	Exposure time	Specie	Value
Ingestion	DL50	OCDE 401	22.000 mg/Kg	-	Rat	Experimental
Skin Contact	DL50	OCDE 402	>2000 mg/Kg.	24 h	Rabbit	Experimental
Inhalation	CL50	OCDE 403	317042 mg/l	2 h	Rabbit	Experimental

Conclusion:

Acute Oral toxicity: Low Acute Dermal toxicity: Low Acute Inhalation toxicity: Low

Corrosion or irritation:

Exposure	Result	Test	Exposure time	Specie	Value
Ingestion	No irritating	OCDE 405	24, 48, 72 h	Rabbit	Experimental
Skin Contact	No irritating	OCDE 404	24, 48, 72 h	Rabbit	Experimental
Skin Contact	Slightly irritating	Patch	24 h	Human	Experimental

06/2017 Safety Data Sheet VT 51 hp Seite 5 von 11

AKOTEC Produktionsgesellschaft mbH | Grundmühlenweg 3 | D - 16278 Angermünde

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



Conclusion:

Not classified as irritating to the skin. Not classified as irritating to eyes.

Respiratory or Skin sensitization:

Exposure	Result	Test	Exposure time	Specie	Value
Skin Contact	not sensitizing	OCDE 429		Rat	Experimental
Skin Contact	not sensitizing	Patch	24 h	Human	Experimental
Inhalation	No relevant				

Conclusion:

No skin sensitizer.

Not available data for respiratory sensitization.

Specific Target Organ Toxicity:

Exposure	Test	Value	Effect	Exposure time	Specie	Value
Ingestion	OCDE 429	1700 mg/Kg Day	No effect	>102 weeks (daily, 5 days/week)	Rat	Experimental
Skin Contact	Patch	0,02 ml (twice a week)	No effect	10 weeks (daily, 5 days/week)	Mouse	Experimental
Inhalation	LOAEC	160 mg/m³	No effect	90 days	Rat	Experimental

Conclusion:

Subchronic dermal toxicity: Low. Subchronic oral toxicity: Low Subchronic inhalation toxicity: Low

Germ cell mutagenicity (in vitro)

Result	Test	Test substrate	Effect	Value

06/2017 Safety Data Sheet VT 51 hp Seite 6 von 11

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



Negative	Others	Bacteria (S.typhimurium)	Experimental
Negative	OCDE 473	Human lymphocytes	Experimental

Carcinogenicity

Exposure	Test	Value	Exposure time	Specie	Valor	Effect
Inhalation	NOAEC	>350 mg/m³ air	18 months	Rat	Experimental	No effect
Skin Contact	NOAEL	0,02 ml (twice per week)		Mouse	Experimental	No effect
Ingestion	NOAEL	1700 mg/Kg.	2 years	Rat	Experimental	No effect
Ingestion	NOAEL	3040 mg/Kg.	105 weeks	Rat	Experimental	No effect
Ingestion	NOAEL	2390 mg/Kg. Day	105 weeks	Mouse	Experimental	No effect

Reproductive toxicity

Study	Test	Valor	Exposure time	Specie	Effect
Effect on fertility	OCDE 416	10100 mg/Kg Day		Mouse	No Effect
Developmental Toxicity	OCDE 414	10400 mg/Kg Day	9 days	Mouse	No Effect

Conclusion CMR

Not classified for carcinogenicity.

Not classified for mutagenic or genotoxic toxicity.

Not classified for reproductive toxicity or developmental toxicity.

12. Ecological data

Data for 1,2 Propanediol

Toxicity

06/2017 Safety Data Sheet VT 51 hp Seite 7 von 11

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



Study	Param eter	Test	Value	Test Time	Specie	Environment
Acute Toxicity fishes	CL50		40613 mg/l	96 h	Oncorhynchus Mykiss	Fresh Water
Acute Toxicity invertebrates	CL50	EPA 600/4 - 90/02 7	18340 mg/l	48 h	Ceriodaphnia Dubia	Fresh Water
Acute Toxicity invertebrates	CL50	FIFR A 72- 3	18800 mg/l	96 h	Americamysis bahía	Sea Water
Threshold limit algae	CE50	OCD E 201	19000 mg/l	96 h	Pseudokirche neriella subcapita	Fresh Water
Threshold limit algae	CE50	OCD E 201	19100 mg/l	96 h	Skeletonema Costatum	Sea Water
Acute Toxicity fishes	ChV	ECOS AR	2500 mg/l	30 days		Fresh Water
Acute Toxicity aquatic invertebrates	NOEC	EPA 600/4 - 89/00	13020 mg/l	7 days	Ceriodaphnia Sp.	Fresh Water
Toxicity aquatic microorganisms	NOEC		20000 mg/l	18 days	Pseudonomas Putida	Fresh Water
Toxicity sedentary organisms	CL50		69836 mg/Kg sediment	10 days	Corophium volutator	Fresh Water

Conclusion

Harmless to fish (CL50 (96h) > 1000 mg/l) Not harmful to invertebrates (CE50 (48) >1000 mg/l) Harmless to algae (CE50 (72h) >1000 mg/l) Harmless to bacteria (CE50 >1000 mg/l)

Persistence and degradability

Biodegradation in water:

Test	Value	Test Duration	Value
OCDE 301F	81,7%	28 days	Experimental

Biodegradation in soil:

06/2017 Safety Data Sheet VT 51 hp Seite 8 von 11

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



Test	Value	Duration	Value	
Others	98%	105 days	Experimental	

Phototransformation aire (DT50 water)

Test	Value	Conc. Radicals OH	Value
AOPWIN v1.92	0,83 days	1.5x10 ⁶ /cm ³	QSAR

Conclusion:

Readily biodegradable in water Biodegradable in soil under anaerobic conditions. Photodegradation in water occurs slowly.

Bioaccumulation potential

Log Pow

Test	Value	Temperature	Value	
OCDE 107	-1,07	20,5°C	Experimental	

Percentage distribution

Test	Air Fraction	Biota Fraction	Sediment Fraction	Soil Fraction	Water Fraction	Value
Level of Mackay III	2,98%		0,07%	48,1%	48,8%	Calculate

Additional information Do not release into natural waters.

13. Disposal considerations

Contaminated packaging

06/2017

Uncontaminated canisters can be re-used. Canisters that cannot be cleaned should be disposed of in the same manner as the contents.

Packaging that cannot be cleaned should be disposed according to the applicable law in the same way that content.

Safety Data Sheet VT 51 hp

•

Seite 9 von 11

AKOTEC Produktionsgesellschaft mbH | Grundmühlenweg 3 | D - 16278 Angermünde

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



Waste code: (91/689 / EEC Commission Decision 2001/118 / EC, O.D. L47 of 16/2/2001): 07 01 0* (other organic solvents, washing liquids and mother liquors); 16 01 14* (antifreeze containing dangerous substances)

LWCA (Netherlands): KGA category 03 Hazardous waste (91/689 / EEC)

Disposal methods: Recycling by distillation Delete incinerator for solvents prior authorization of pollution control agency to discharge water treatment station

No discharge into surface water

Packaging / Container:

Waste material code packaging (91/689 / EEC Commission Decision 2001/118 / EC, O.D. L47 of 16/2/2001): 15 01 10 * (packaging containing residues of hazardous substances or contaminated by them)

Disposal of contaminated packaging: Completely empty containers Disposal in an authorized waste collection point Recommended cleaning method: cleaned by recycling center or specialized company

14. Transport information

Not classified as hazardous under transport regulations. (ADR / RID / ADNR / IMDG/GGVSee ICIAO/IATA)

15. Regulatory information

Regulations of the European Union (labeling) / National legislation / Regulations:

Hazard symbol H-phrases: P-phrases:

06/2017 Safety Data Sheet VT 51 hp Seite 10 von 11

AKOTEC Produktionsgesellschaft mbH I Grundmühlenweg 3 I D - 16278 Angermünde

T: +49 (0) 3331 25 71 63 0 | F: +49 (0) 3331 25 59 99 6 | M: info@akotec.eu | W: akotec.eu



16. Further information

Abbreviations and acronyms:

PNEC: Predicted No Effect Concentration.

Intermittent Release: Intermittent but only recurring infrequently i.e. less than once per month and for no more than 24 hours.

This safety data sheet is intended to provide information and recommendations as to: 1. how to handle chemical substances and preparations in accordance with the essential requirements of safety precautions and physical, toxicological and ecological data. 2. How to handle, store, use and transport them safety.

No liability for damage occurred in connection with the use of this information or with the use, application, adaptation or processing the products here described will be accepted. No liability will be accepted for damage indirectly incurred.

We provide this information data according to our present level of knowledge and experience. No assurances concerning the characteristics of our product are hereby furnished.

06/2017

Safety Data Sheet VT 51 hp

Seite 11 von 11